MID-MATIC™ SERIES



The 1.5" (38mm) MID-MATIC automatic nozzle series includes a wide flow range and multiple operational pressure choices. Models feature flush without shutting down, your choice of molded rubber bumper with "power fog" teeth or stainless steel spinning teeth, detent flow control, "Gasket Grabber" inlet screen, and patented TFT slide valve. MID-MATIC's are also available with TFT's IMPULSE™ trigger valve system.

FULLY AUTOMATIC



Integrating TFT's patented slide valve, you always get turbulence free flow control and a powerful stream even in changing water supply conditions. Models also include an integrated debris screen to prevent stream quality degradation.

FLOW AND **PRESSURE CHOICES**



The MID-MATIC offers a wide flow range of 70-200 gpm (260-760 l/min) and operational pressure choices of 100, 75 or 55 psi (7, 5 or 3 bar).



POWER FOG OR SPINNING



Your choice of molded rubber bumper with "power fog" teeth or stainless steel spinning teeth design.









Models are available both with or without shutoff and are paired with a separate ball valve or valved playpipe. Ideal for breakand-extend operations. (38mm) rigid rocker lug-coupling is standard.



HM-TO TIP ONLY 70-200 gpm (260-760 l/min) 100 psi



Shut-Off valve is offered separately

> HMK-STO TIP ONLY WITH SHUT-OFF 70-180 gpm (260-680 l/min) 55 psi



Models are available with or without a pistol grip and also include six detent flow positions.

Colored pistol grip and handle covers are available, as well as folding pistol grips.

The innovative integration of a trigger actuator with TFT's turbulence free slide valve, provides complete nozzle operator flow control with only a single hand, allowing the other hand to consistently control stream pattern selection.



When applicable, colored pistol grips are available for MID-MATIC(s) on this page, including folding pistol grips and colored bail handle covers.

