

RAMXD™



LOWER ATTACK ANGLE • SELF STABILIZING • LIGHTWEIGHT

RAMXD™

DELIVERS



- Low 75 psi (6 bar) operating pressure
- Lightweight at only 19 lbs (8.6 kg)

HIGH RISE DEPLOYMENT





SINGLE FIREFIGHTER OPERATION

- Low 14 degree attack angle
- Big Water... Fast!
500 GPM
(2000 L/min)



EXTEND/MANIFOLD APPLICATION



EXPOSURE PROTECTION

- Large surface area with 4 forged legs
- Minimal friction loss of 9 psi (.62 Bar)



SPECIFICATIONS

| | |
|---|--|
| Flow | Up to 500 GPM (2000 L/min) |
| Operating Pressure | 75 psi (6 bar) |
| Up-Down Travel Range | 14° - 51° |
| Left-Right Travel Range | 20° each way, 40° total |
| Inlet Size | 2.5" (65mm) |
| Outlet Size | 2.5" (65mm) |
| Folded Size | 16.22" L x 8.42" W x 8.76" H (41.19 L x 21.38 W x 22.25 H (cm)) |
| Weight (Monitor Only) | 19 lbs (8.6 kg) |
| Weight (RAN Fog Nozzle w/ Stream Shaper) | 22 lbs (9.9 kg) |
| Weight (Deluge Tip w/ Stream Shaper) | 21 lbs (9.5 kg) |
| Friction Loss | 9 psi (.62 bar) |
| Footprint Area | 448 in ² (2890 cm ²) |
| Legs | 4 |
| Warranty | 5 years |

ACCESSORIES:

| | | |
|---|---|--|
|  |  |  |
| 3896 RAN FOG NOZZLE | 181A DELUGE TIP | 282A MINI STREAM SHAPER |
|  |  |  |
| 197A STACKED TIP | 3896MB MOUNTING BRACKET | HF500 HYDROFOAM NOZZLE |

SEE VIDEOS AT:



www.brasstackshardfacts.com