

RAMXD™



LOWER ATTACK ANGLE • SELF STABILIZING • LIGHTWEIGHT

RAMXD™

DELIVERS



- Low 75 psi (6 bar) operating pressure
- Lightweight at only 19 lbs (8.6 kg)

HIGH RISE DEPLOYMENT





SINGLE FIREFIGHTER OPERATION

- Low 14 degree attack angle
- Big Water... Fast!
500 GPM
(2000 L/min)



EXTEND/MANIFOLD APPLICATION



EXPOSURE PROTECTION

- Large surface area with 4 forged legs
- Minimal friction loss of 9 psi (.62 Bar)



SPECIFICATIONS

Flow	Up to 500 GPM (2000 L/min)
Operating Pressure	75 psi (6 bar)
Up-Down Travel Range	14° - 51°
Left-Right Travel Range	20° each way, 40° total
Inlet Size	2.5" (65mm)
Outlet Size	2.5" (65mm)
Folded Size	16.22" L x 8.42" W x 8.76" H (41.19 L x 21.38 W x 22.25 H (cm))
Weight (Monitor Only)	19 lbs (8.6 kg)
Weight (RAN Fog Nozzle w/ Stream Shaper)	22 lbs (9.9 kg)
Weight (Deluge Tip w/ Stream Shaper)	21 lbs (9.5 kg)
Friction Loss	9 psi (.62 bar)
Footprint Area	448 in ² (2890 cm ²)
Legs	4
Warranty	5 years

ACCESSORIES:

		
3896 RAN FOG NOZZLE	181A DELUGE TIP	282A MINI STREAM SHAPER
		
197A STACKED TIP	3896MB MOUNTING BRACKET	HF500 HYDROFOAM NOZZLE

SEE VIDEOS AT:



www.brasstackshardfacts.com