SUPER VAC AMCA CERTIFIED PRODUCTS

VALOR BATTERY PPVs

Super Vacuum Manufacturing Company, Inc. certifies that the positive pressure ventilators listed below are licensed to bear the AMCA (Air Movement and Control Association) Seal. The listed ratings are based on tests and procedures in accordance with AMCA Standard 240 and comply with the AMCA Certified Ratings Program.

For more than 100 years, AMCA has been a recognized authority for the development of standards and measurement of air movement.



Specifications and AMCA-Certified Performance Ratings

Model	Blade	Power	HxWxD	Motor	Weight	RPM	Setback	Angle	Output
V16-BD	16"	1 Hp	23.75" x 22.5" x 11.75"	Variable-Speed DC	34 lbs	2,627	14 ft	5°	9,816 cfm
			591 mm x 572 mm x 298 mm		15 kg		4.3 m		16,677 cmh
V18-BD	18"	1 Hp	25.75" x 25.75" x 11.75"	Variable-Speed DC	46 lbs	2,032	15 ft	10°	10,840 cfm
			654 mm x 654 mm x 298 mm		21 kg		4.6 m		18,417 cmh

Certification is for Installation Type A - Free Inlet, Free Outlet and does not include the use of accessories and their effects.



MORE ABOUT OUR DEWALT POWERED PPVS

PATENT PENDING

The all-new Super Vac 16" & 18" variable-speed battery fans are equipped with dual DeWalt FLEXVOLT® batteries, making them the most swappable PPV interface on the market. This patent pending design also offers 180 degrees of tilt, providing every attack angle, including positive and negative, as well as attic and manhole deployment.

Features a tough yet lightweight aluminium frame to protect key components while providing a compact lightweight design.









