



WE INNOVATE EVERY DAY.
e-one.com

TYPHOON® CHASSIS



CLASSIC STYLE WITH MODERN REFINEMENTS

The E-ONE Typhoon® cab features a rugged design with superior ride and handling. The aluminum cab is built with heavy wall extrusions and 3/16" plate for walls, floor, roof and doors for maximum durability. The Typhoon is available in five cab lengths with either a flat roof or one of four raised "vista" roof designs along with hundreds of options to meet your department's needs.

The Typhoon cab provides excellent visibility for driver and crew with its low profile dash, radial sweep wipers, one piece door glass and a reduced profile interior A/C system. Built to last, the Typhoon C-frame chassis has galvanized powder-coated rails and Geomet® coated hardware for corrosion resistance. E-ONE cabs are extensively tested to ensure superior performance to keep your crew safe. Contact your local dealer to learn more about the E-ONE Typhoon cab.

OUR VEHICLES CONNECT AND PROTECT
PEOPLE AROUND THE WORLD EVERY DAY.
www.revgroup.com





CHASSIS

- 330-600 HP Cummins® engines
- Allison® EVS 3000, 4000 or 4500 transmission
- Up to 24,000 lb. front and 62,000 lb. rear GVW rating
- Up to 430 AMP (single) or 640 AMP (dual) alternators
- 45-degree cramp angle
- Front disc brakes with ABS
- Taper leaf spring front suspension and multi-leaf rear suspension
- C-frame chassis have galvanized and powder coated 110,000 psi high strength steel frame rails

CAB

- All aluminum cab constructed with four-sided seamless extrusions interlocked and welded to 3/16" aluminum plating on the floors, rear walls, side walls, roof and doors
- Heavy wall cab sub-frame welded to a front C-Channel extrusion and reinforced by multiple cross members below rear cab floor
- Roll cage cab design supports more than 5x the roof load of NFPA/SAE requirements
- Severe duty cab interior with cast aluminum dash and hinged aluminum overhead console
- Seating for up to 10

OPTIONS

- 44.5", 58", 67.5", 74" or 80" cab lengths
- Full length or barrier style doors
- 12", 16", 20" or 24" vista roof heights; 12" split-raised roof for aerials
- Interior, exterior, or dual access medical cabinets
- 4Front™ and RollTek™ airbag systems
- Rear disc brakes (up to 27 K)
- G4™ Electronic Stability Control
- OnGuard™ Collision Mitigation
- Independent Front Suspension (IFS) with up to 48-degree cramp angle
- Air ride rear suspension
- Optional 12" frame rails with full C-channel reinforcement (if required)

- Various bumper styles including polished stainless steel and severe-duty painted steel C-channel
- 12" to 28" bumper extensions with options that include trays, reels, and cut-in crosslays
- Clean cab options include external transverse compartments for bunker gear and SCBA storage as well as over front wheel exterior access compartments

WARRANTY

- Lifetime structural warranty on frame that includes crossmembers
- 25 year frame rail corrosion warranty
- 10 year structural warranty on cab

